

VITRA

AIR VARIATOR

FOR THE VITRA
C-SERIES

VITRA | RED3410



Lindholdt Maskiner A/S
Industrivej 8
DK-6818 Årre

Telefon: +45 76 77 44 77
E-mail: info@lindholdt-maskiner.dk
Web: www.lindholdt-maskiner.dk

MADE IN DENMARK
..designed for the world!



ENVIRONMENTALLY FRIENDLY

Weed control without pesticide use



MINIMAL FIRE HAZARD

No use of open flames



LOW GAS CONSUMPTION

Gas consumption only 2.5 kg/hour



From the touchscreen control in the cabin, there is a quick overview of the system and easy control of the unit.



The innovative side burners ensure effective weed control very close to, for example, house walls and curbs, without the risk of collision.



As an option, the system can be delivered with a hydraulic lateral shift, with the option to shift the unit sideways 180 mm. to each side.

AIR VARIATOR

VITRA C-SERIES | RED3410

WeedControl Air Variator is not only environmentally friendly but also economically the best alternative to chemical weed control.

The system works exclusively with hot air, and therefore operates without an open flame, and the risk of fire is therefore minimal.

The Air Variator exposes the unwanted plant to 380°C hot air, which heats the plant cells to 75°C so that they burst and the plant cannot absorb nutrients, causing the entire plant to die.

The innovative side burners make it possible to fight weeds up close by e.g. house walls or the curb and as an option, the system can be supplied with a hydraulic lateral shift, which allows the system to be shifted laterally by 180 mm. to each side.

The system can be delivered with an integrated tank system which can also be mounted on the back of the machine, which ensures optimum driving comfort and manoeuvrability. Alternatively, a coupling for standard gas bottles can be fitted.

With recirculation of the hot air, a gas saving of approx. 60% compared to other similar weed burners and with a gas consumption of only 2.5 Kg per hour, this system is described as one of the most Co² friendly ways to fight weeds.

MODEL	RED3410
Working width:	1000 mm.
Working temperature:	380°C
Gas consumption:	2,5 Kg/t
Co ₂ :	9,5 Kg/t
Capacity:	2500-3500 m ² /t
Weight:	235 Kg. *

* Weight excl. gas tanks

For additional data, please see the price list.

Your local Vitra dealer:



© 2022 All rights reserved Lindholdt Maskiner A/S
This data sheet is protected by international copyright laws.

No part of this data sheet, including images and text, may be reproduced, distributed, translated or transmitted in any form or by any means, electronic or mechanical, including photocopy or reproduction, without the prior written permission of Lindholdt Maskiner A/S.