

# VITRA

## DISC SPREADER

FOR THE VITRA  
C-SERIES

VITRA | RED2810 / RED2820



Lindholdt Maskiner A/S  
Industrivej 8  
DK-6818 Årre

Telefon: +45 76 77 44 77  
E-mail: [info@lindholdt-maskiner.dk](mailto:info@lindholdt-maskiner.dk)  
Web: [www.lindholdt-maskiner.dk](http://www.lindholdt-maskiner.dk)

MADE IN DENMARK  
..designed for the world!



## DISC SPREADER

Adjustable spreading of up to 6 metres



## HYDRAULIC AGITATOR

Ensures a uniform spread



## QUICK MOUNTING

Mounted with Vitra Quick-shift



The spreader is equipped with a hydraulic agitator, which ensures an even distribution and uniform spreading.



The dosage amount is easily and simply adjusted using a handle that is easily accessible on the spreader.



The strong construction with stainless disc with adjustable "wings" and width adjustment ensures a perfect result.

# DISC SPREADER

VITRA C-SERIES | RED2810 / RED2820

With this series of functional plate spreaders, you get a good and economical attachment for effective control of slippery roads.

With adjustable spreading width from 1 and up to 6 metres, and a dosage from 10g/m<sup>2</sup> which is easily adjusted with two handles on the spreader, a flexible solution is achieved that can be used with many different spreading materials. As an option, the spreader can be delivered with both hydraulic width and volume control as well as speed-related control.

The spreader is available with a capacity of either 125 or 250 l. It is built with a strong plastic container mounted on a lacquered steel chassis and with disc and adjustment made of stainless steel. As option the chassis can be delivered in stainless steel.

MODEL	RED2810 (RED2812*)
Length x Width:	910 x 910 mm.
Height:	900 mm.
Working width:	1000 - 6000 mm.
Volume:	125 l.
Weight:	91 Kg.

MODEL	RED2820 (RED2822*)
Length x Width:	1120 x 1120 mm.
Height:	1090 mm.
Working width:	1000 - 6000 mm.
Volume:	250 l.
Weight:	96 Kg.

\* With stainless steel chassis

For additional data, please see the price list.

Your local Vitra dealer:



© 2022 All rights reserved Lindholdt Maskiner A/S  
This data sheet is protected by international copyright laws.

No part of this data sheet, including images and text, may be reproduced, distributed, translated or transmitted in any form or by any means, electronic or mechanical, including photocopy or reproduction, without the prior written permission of Lindholdt Maskiner A/S.