

# VITRA

VITRA | FEG1100 / FEG1300 / FEG1500

## SNOW SWEEPER

FOR THE VITRA  
C-SERIES



Lindholdt Maskiner A/S  
Industrivej 8  
DK-6818 Årre

Telefon: +45 76 77 44 77  
E-mail: [info@lindholdt-maskiner.dk](mailto:info@lindholdt-maskiner.dk)  
Web: [www.lindholdt-maskiner.dk](http://www.lindholdt-maskiner.dk)

MADE IN DENMARK  
..designed for the world!

# SNOWSWEEPER

VITRA C-SERIE | FEG1100 / FEG1300 / FEG1500

With this hydraulic center-driven snow sweeper with a unique centered swing system, we offer a brush optimized to Vitra's high performance, but also its compact dimensions. With the unique hydraulic center swing, it is possible to adjust the working angle, without side offset the sweeper. This means that the sweeper does not have to be wider than the machine to make sure it sweeps the machine free when it is angled.

The robust structure, as well as the high corrosion resistance in the paintwork, ensures in part an efficient utilization of Vitra's high performance, but also a sweeper that lasts for many hours of work for many years.

As the frame does not need to be separated during replacement of worn brush rings, a quick replacement is ensured. The brush is divided into two brush roll halves, each driven by a center mounted oil engine.

MODEL	FEG1100
-------	---------

Total / Working width:	1100 mm.
------------------------	----------

Height x Length:	647 x 908 mm.
------------------	---------------

Weight:	160 Kg.
---------	---------

MODEL	FEG1300
-------	---------

Total / Working width:	1300 mm.
------------------------	----------

Height x Length:	647 x 908 mm.
------------------	---------------

Weight:	170 Kg.
---------	---------

MODEL	FEG1500
-------	---------

Total / Working width:	1500 mm.
------------------------	----------

Height x Length:	647 x 908 mm.
------------------	---------------

Weight:	180 Kg.
---------	---------

*For additional data, please see the price list.*

Your local Vitra dealer:



## LARGE BRUSH DIAMETER

600 mm. brush diameter



## HYDRAULIC SWING

Hydraulic angle adjustment



## QUICK MOUNTING

Standard A-frame



*Solid support wheels ensure efficient and optimal sweeping as well ensure that minimal brush wear occurs during use.*



*Splitting the two brush roll halves saves a lot of time and ensures a quick replacement of brush rings.*



*The brush guard is equipped with rubber edges that protect against damage in the event of a collision.*